

TR-900

Radial technology
to boost your business



TIRE LIFE



PUNCTURE RESISTANCE



COOL RUNNING



LONGER DISTANCE



STABILITY

Built to excel in demanding applications, the TR-900 delivers relentless performance. Engineered for low rolling resistance, the TR-900 optimizes energy efficiency, thereby maximizing operational cost savings. This premium, radial tire is ideal for high-speed and long-distance use. Its large footprint reduces stress, maximizes tire life, thus minimizing machine downtime and keeping you on the move. An anti-slip bead and a unique compound ensure exceptional grip and handling, allowing for faster load positioning and precise cornering.

The shock-absorbing structure, with reinforced sidewalls and rim guards, tackles challenging environments with ease, protecting against impacts and punctures.

TR-900

RADIAL PNEUMATIC - MAXIMUM INTENSITY APPLICATIONS

TREAD PATTERNS



TR-900
16.00R25



TR-900

Size	Alternative Size	Rim	Product Dimensions [mm]			Minimal Dual Spacing [mm]	Inflation Pressure [bar]	Tire Type	Load Index	Speed Symbol	Load Capacity [kg]	
			Overall Diameter	Section Width	Tread Depth						Counterbalanced Lift Trucks up to 25 km/h	
											Load Wheel	Steering Wheel
5.00R8		3.00D-8	468	137	25	158	10	TT	111	A5	1.415	1.090
6.00R9		4.00E-09	540	162	25	192	10	TT	121	A5	1.885	1.450
6.50R10		5.00F-10	585	180	27	212	10	TT	128	A5	2.340	1.800
7.00R12		5.00S-12	670	190	28	230	10	TT	136	A5	2.915	2.240
28x9R15	225/75R15 (8.15R15)	7.0-15	706	230	25	248	10	TT	149	A5	4.225	3.250
7.00R15	29x8R15	5.5-15	736	195	28	236	10	TT	143	A5	3.540	2.725
250R15	250/70R15	7.0-15	736	252	27	282	10	TT	153	A5	4.745	3.650
300R15	315/70R15	8.0-15	835	312	36	345	10	TT	165	A5	6.695	5.150
8.25R15		6.5-15	838	232	32	281	10	TT	153	A5	4.745	3.650
10.00R20	290/95R20	7.5-20	1.062	294	35	334	10	TT	166	A5	6.890	5.300
12.00R20	330/95R20	8.5-20	1.136	320	41	378	10	TT	176	A5	9.230	7.100
12.00R24	330/95R24	8.5-24	1.232	322	39	378	10	TT	178	A5	9.750	7.500
14.00R24	385/95R24	10.0-24	1.416	390	64	450	10	TT/TL	193	A5	14.950	11.500
16.00R25	445/95R25	11.25-25	1.495	424	56	529	10.00	TT	200	A5	18.200	14.000
18.00R33		13.00-33	1.838	497	74	598	10	TT	214	A5	27.560	21.200

Subject to technical amendments, printing errors and mistakes in text or illustrations. 10.24



Follow us



Yokohama TWS S.p.A.
Via Nazionale Tiburtina, 143 - 00019 Villa Adriana - Tivoli (RM), Italy
Phone: +39 0774 3841 – info.tws@yokohama-tws.com
www.trelleborg-tires.com



Shop our tires online



Discover our website