

# Twin Implement. Universal begabt.



# Twin Implement

Baureihe mit geringem Bodendruck für Landmaschinen in schweren und herausfordernden Einsätzen.

Reifengröße		Betriebskennung (LI/SI)		Profil	Neureifen		Reifen im Betrieb		SLR	RC	Felge
					SW mm	OD mm	SW (max) mm	OD (max) mm	mm	mm	
280/60-15.5	TL	115A8 103A8		T421	260	730	275	747	325 335	2142 2163	AG8.00
280/60-15.5	TL	125A8 113A8		T421	272	736	278	747	331	2194	AG8.00
280/60-15.5	TT	128A8		T478	260	730	275	747	325	2142	AG8.00x15.5
400/60-15.5	TL	145A8 132A8		T404	400	875	436	907	384 396	2568 2594	AG13.00
400/60-15.5	TL	148A8 136A8		T404	410	875	436	907	384 396	2568 2594	AG13.00
400/60-15.5	TL	145A8		T478	400	875	436	907	384	2598	AG13.00x15.5
420/55-17	TL	133A8 121A8		T421	415	898	420	912	397 404	2667 2685	13.00
420/55-17	TL	145A8 133A8		T421	in Vorbereitung						
400/55-17.5	TT	131A8 119A8		T404	400	880	420	902	388 400	2583 2609	AG11.75
400/55-22.5	TL	147A8 135A8		T404	400	1000	420	1021	450 460	3035 3045	AG11.75
500/45-22.5	TL	146A8 134A8		T404	500	1020	528	1042	450 465	3020 3050	AG16.00
500/60-22.5	TL	155A8 143A8		T404	500	1170	528	1200	500 530	3490 3510	AG16.00
500/60-22.5	TL	155A8 143A8		T421	500	1170	528	1200	525 545	3490 3510	AG16.00
560/45-22.5	TL	154A8 142A8		T404	540	1075	609	1111	475 490	3235 3245	AG16.00
560/60-22.5	TL	158A8 145A8		T404	564	1235	609	1291	525 541	3675 3685	AG16.00
560/60-22.5	TL	167A8 155A8		T404	564	1235	609	1291	525 541	3675 3685	AG16.00
600/50-22.5	TL	156A8 144A8		T404	610	1170	638	1214	520 540	3460 3500	AG20.00
600/50-22.5	TL	156A8 144A8		T423	600	1170	630	1214	520 540	3460 3500	AG20.00
600/50-22.5	TL	165A8 153A8		T404	610	1170	638	1214	510 530	3470 3510	AG20.00
600/50-22.5	TL	168A8 156A8		T404	610	1170	638	1214	500 520	2480 3520	AG20.00
710/40-22.5	TL	158A8 146A8		T404	710	1160	773	1179	510 525	3460 3470	AG24.00
400/60-26.5	TT	147A8 135A8		T404	400	1160	425	1187	525 540	3470 3490	AG13.00
600/55-26.5	TL	166A8 154A8		T404	620	1360	638	1379	595 619	3970 4000	AG20.00
600/55-26.5	TL	166A8 154A8		T421	600	1350	638	1379	595 619	3970 4000	AG20.00
710/45-26.5	TL	169A8 157A8		T404	710	1350	773	1384	600 620	3980 4000	AG24.00
710/45-26.5	TL	169A8 157A8		T423 MK2	710	1350	773	1384	590 610	3970 4020	AG24.00
800/40-26.5	TL	172A8 159A8		T404	800	1350	840	1379	590 610	3970 4020	AG28.00
800/40-26.5	TL	172A8 159A8		T423 MK2	800	1350	840	1379	600 620	3970 4010	AG28.00
650/65-30.5	TL	173A8 161A8		T404	660	1650	697	1679	710 740	4830 4860	AG20.00
710/50-30.5	TL	175A8 163A8		T404	727	1500	773	1534	650 680	4425 4455	AG24.00
710/50-30.5	TL	175A8 163A8		T423	730	1500	773	1534	660 690	4425 4455	AG24.00
750/60-30.5	TL	178A8 166A8		T404	750	1650	804	1738	710 740	4830 4870	AG24.00
800/45-30.5	TL	178A8 166A8		T404	800	1500	862	1545	650 670	4455 4485	AG28.00
800/45-30.5	TL	178A8 166A8		T423	800	1500	840	1536	660 680	4420 4460	AG28.00
850/50-30.5	TL	179A8 167A8		T404	850	1650	920	1684	691 723	4840 4880	AG28.00



Yokohama TWS Germany GmbH  
Helmholtzstraße 1 | 64711 Erbach | Germany  
tws.erb.info@yokohama-tws.com

Yokohama TWS Austria GmbH  
Am Teich 1 | 4300 Sankt Valentin | Austria  
tws.at.info@yokohama-tws.com

Yokohama TWS Switzerland GmbH  
Bertswilstrasse 52 | 6023 Rothenburg | Switzerland  
tws.ch.info@yokohama-tws.com

www.trelleborg-tires.com

Folgen Sie uns

