



HPS Solidflex
Traction

HPS Solidflex
Smooth

HPS Smooth

PREMIUM CONSTRUCTION SOLID

BRAWLER™ HPS SKID STEER

The Brawler™ HPS (High Performance Solid) Skid Steer tires are designed to perform in extreme environments including scrap metal recycling, waste transfer stations and mining operations.

The Brawler™ HPS Solidflex features elliptical apertures to deliver a comfortable ride resulting in reduced equipment and operator fatigue.

FEATURES AND BENEFITS

- Excellent traction
- Durable cut-resistant rubber compound eliminates downtime caused by flats and sidewall cuts
- Press on to flat-based wheels
- Deep lug tread design offers three times more wear than a pneumatic tire
- Steel base rings ensure strict rim adherence

APPLICATIONS

- Waste Transfer Stations
- Metal Recycling
- Construction & Demolition
- Steel Mills & Foundries
- Heavy Industrial
- Quarries and Open Pit Mining
- Underground Mining

PREMIUM CONSTRUCTION SOLID
BRAWLER™ HPS
SKID STEER

HPS SOLIDFLEX TRACTION

Tire Size	Pneumatic Equivalent Size	Rim Size	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Load Capacity 6 mph (lbs)	Weight (lbs)
31x10-20	10-16.5	7.5-20	30.9	10.0	52	6,205	153
33x12-20	12-16.5	7.5-20	33.1	11.2	71	6,550	207
36x14-20	14-17.5	7.5-20	36.0	14.0	89	7,295	303
40x14-20	15-19.5	10.0-20	40.0	14.0	118	10,925	446

HPS SOLIDFLEX SMOOTH

Tire Size	Pneumatic Equivalent Size	Rim Size	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Load Capacity 6 mph (lbs)	Weight (lbs)
31x10-20	10-16.5	7.5-20	30.9	10.0	52	6,205	166
33x12-20	12-16.5	7.5-20	33.1	11.2	71	6,550	227
36x14-20	14-17.5	7.5-20	36.0	14.0	89	7,295	341
40x14-20	15-19.5	10.0-20	40.0	14.0	118	10,925	493

HPS SMOOTH

Tire Size	Pneumatic Equivalent Size	Rim Size	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Load Capacity 6 mph (lbs)	Weight (lbs)
31x10-20	10-16.5	7.5-20	30.9	10.0	52	8,280	173
33x12-20	12-16.5	7.5-20	33.1	12.0	71	8,730	231
36x14-20	14-17.5	7.5-20	36.0	14.0	89	9,735	351
40x14-20	15-19.5	10.0-20	40.0	14.0	118	14,560	506

**Notes: Tread depth on smooth tires indicates wearable rubber.
 All Brawler™ HPS tires are available as either an assembly or as tire only.**



Yokohama TWS North America, Inc.
 107 Audubon Road - Building 2 - Suite 205
 Wakefield, MA 01880
 800-948-8473
 info.tws@yokohama-tws.com
 www.trelleborg-tires.com/en-us

Follow us

